

6.

Survey No. 3942--continued.

The S. E. Cor. Sec. 12, T. 30 S., R. 64 E., M.D.M., is a rock about 12x12x18 ins., set in a mound of rock, chiseled with four notches on the south face and two notches on the north face. This is the nearest standing corner of the public survey that can be found and identified.

Sur. No. 3936, Golden Rod No. 1 lode;-- Cor. No. 1 is a pine post, properly set and scribed with the number of the corner and survey and the initial of the claim.

NOTE;-- The discrepancies between these field notes and the several certificates of location are due to errors in the latter.

An open cut, the mouth of which bears from a point on line 2-7, 105.4 ft. from Cor. No. 2, S. 8.38° E., W. 116.62 ft., 5 ft. wide, running S. 40° 30' E. 15 ft. to 10 ft. face. In solid rock.

A shaft which bears from a point on line 2-7, Bellvue No. 2 lode, 129.5 ft. from Cor. No. 2, W. 84° 13' E. 107.6 ft., 3 x 8 ft., 10 ft. deep. In solid rock.

An open cut, the mouth of which bears from a point on line 2-7, Bellvue No. 2 lode, 129.5 ft. from Cor. No. 2, S. 88° 10' W. 156 ft., 8 ft. wide, running N. 57° 30' W. 10 ft. to 10 ft. face. In solid rock.

All of said improvements are in an unusually hard granite formation.

OTHER IMPROVEMENTS.

There are no other improvements on this claim.

INSTRUMENT.

This survey was made with a Bull and Bull mining transit No. 4634. The courses were deflected from the true meridian as determined by observation on Polaris at western elongation. The distances were measured with 100-ft. and 500-ft. steel tapes.

REPORT.

The lode line of each location of this claim was run directly upon the ground, and the several corners established by means of offsets from the lode lines. All the lines were run either directly upon the ground or by traverses, run upon the ground and submitted in a separate report herewith.