

Feet

275 ft., 5x6 ft. running S. 45° E., 80 ft. to face.

Value \$720.00

3

Shaft, which bears from Cor. No. 3, S. 87° 30' E., 325 ft., 5x6 ft. 100 ft. deep.

Value \$2,000.00

Total expenditure

\$2845.00

 Other Improvements

None.

 Instrument.

This survey was made with a Berger transit. The courses were deflected from the true meridian as determined by solar observation.

Distances were measured with a 500 ft. steel tape.

NOTE:- The disagreements between these field notes and the location certificates are due to errors in the latter.

 REPORT.

The N. E. Cor. Sec. 24, T. 6 N. R. 49 E., M.D.M. is a granite stone 9x14 ins. 8 ins. above ground marked with 3 notches on the South and 3 notches on the North face.

Line 2-3 sur. No. 37, 2 G. Lode is S. 20° 31' W. 402.7 ft. instead of S. 21° W., 400 ft.

Bearing of line 4-1 Surs. No. 37 and 44 2nd Extension East 2 G. Lode is N. 20° 31' E., instead of N. 20°30' E.

Tie from Cor. No. 1 Surs. No. 37 and 44 2nd. Extension East 2 G. Lode is N. 0° 35' W., 1799.2 ft., instead of North 1798 ft.

Tie from Cor. No. 1 Surs. No. 37 and 44 2nd Extension East 2 G. Lode to Cor. No. 2 Sur. No. 37 2 G. Lode is N. 59° 32' W., 754 ft., instead of N. 59° 15' W., 750 ft.

Tie from Cor. No. 1 Sur No. 3947 Mayflower Lode to N.E. Cor. Sec. 24, T. 6. N. R. 49 E., M.D.M. is N. 77° 10' E. 2553.2 ft.