

SURVEY No. 3993.

R E P O R T .

The lode line of each location of this claim was run directly upon the ground, and the corners were established by means of offsets from the lode lines. All tie lines were run directly upon the ground.

The S. 1/4 Cor., Sec. 36, T. 46 N., R. 53 E., M. D. B. & M., is a granite stone chiseled with 1/4 on the North face, with a mound of earth alongside. This is the nearest standing corner of the public survey that I was able to find, after diligent search.

Sur. No. 3986, Silver Bug lode:

Cor. No. 1 is a pine post, properly set and scribed with the initials of the lode, number of the corner and number of the survey.

Sur. No. 3992, Soft Snap lode:

Cor. No. 2 is a pine post, properly set and scribed with the initials of the lode, number of the corner and number of the survey.

Silver Bell lode, unsurveyed:

All of the corners are cottonwood posts, 4 ins. square, set in mounds of earth and properly scribed.

May Flour lode, unsurveyed:

All of the corners are cottonwood posts, 4 ins. square, set in mounds of earth and properly scribed.

NOTE.---The location certificates of the locations embraced in this claim are defective inasmuch as they do not give correct bearings of the lines; but I found all corners standing and properly marked.

OTHER IMPROVEMENTS.---None.

INSTRUMENTS.

This survey was made with a Gurley solar transit. The courses were deflected from the true meridian as determined by direct solar observations. The distances were measured with 500-ft. and 10-ft. steel tapes.