Feet Survey No. 4080.

EXPENDITURE OF FIVE HUNDRED DOLLARS.
Continued.

No. 3 A cut, the easterly end of which bears from corner No. 5 Edwin No. 2 lode, S. 24°15' W. 431 feet, running N. 75°30' W., 20 feet by 3 feet by 3 feet face, the northerly side being the mouth,
Value $ 35.00

No. 4 A shaft, the northeasterly side of which bears from corner No. 5 Edwin No. 2 lode, S. 25°10' W., 453 feet, 4 feet by 8 feet by 10 feet,
Value $ 75.00

No. 5 A cut, the mouth of which bears from corner No. 5 Edwin No. 2 lode, S. 6°50' W. 422 feet, running N. 58°30' W., 5 feet by 12 feet by 10 feet face,
Value $ 50.00

No. 1 The discovery cut of the Edwin No. 5 lode, the mouth of which bears from corner No. 2, Edwin No. 5 lode, N. 35°55' W. 352 feet, running N. 23°30' W., 13½ feet by 9½ feet by 6 feet face,
Value $ 35.00

No. 2 A cut and tunnel, the mouth of which bears from corner No. 1, Edwin No. 5 lode, S. 72°15' E. 308 feet, running N. 38°15' E. 32 feet to a point, thence N. 66°35' E. 28 feet to face of tunnel, cut 5 feet by 15 feet by 10 feet face; tunnel 4½ feet by 6½ feet by 45 feet long,
Value, cut and tunnel $ 500.00

Other Improvements
None

Instrument.

This survey was made with a C. L. Berger and Sons' mining transit No. 3942. The courses were deflected from the true meridian as determined by direct solar observation. The distances were measured with 100 feet and 500bfeet steel tapes.

REPORT.

The lode line of each location of this claim was run directly upon the ground, and the several courses established by means of offsets from the lode lines. The side lines were then measured. All tie lines were run either directly upon the ground or by traverses run upon the ground and submitted in a separate report herewith.

The S.E. corner of Section 31, T. 13 N., R. 25 E., M.D.B. and M. is a basalt rock, 4 inches by 6 inches, 9 inches above the ground, marked by 5 notches on the easterly corner and one notch on the westerly corner. This is the nearest standing corner of the public survey which could be found.

Amended survey No. 3814, Dipper lode.

Corners Nos. 1-2-3 and 4 are pine posts, set in the ground, properly scribed with the number of the corner and survey. I find the courses and distances of lines 1-2, 2-3, 3-4 and 4-1 to be correct as approved.

The disagreements between the courses and distances as