

- No. 3. A shaft which bears from a point on line 2-3, Valley lode, 623 ft. from Cor. No. 2 N.72°43'E. 251 ft., 4x7 ft., 47 ft. deep. In rock. Value, \$470.00
- No. 4. A shaft which bears from a point on line 2-3, Valley lode, 623 ft. from Cor. No. 2 N.38°35'E. 217 ft., 4x6 ft., 13 ft. deep. In gravel and rock. Value, \$100.00
- No. 5. A shaft which bears from a point on line 2-3, Valley lode, 623 ft. from Cor. No. 2 N.34°58'W. 337 ft., 5x8 ft., 11 ft. deep. In rock. Value, \$110.00

#### OTHER IMPROVEMENTS.

A corrugated iron building, the S. E. Cor. of which bears from Cor. No. 4, Goodenough lode, N.74°27'W. 139.3 ft., 14x16 ft., course of long sides N.84°W. In the center of the east end there is a frame addition 11x12 ft., course of long sides N.84°W. Belongs to claimant herein.

#### INSTRUMENT.

This survey was made with a Buff and Buff mining transit No. 4604. The courses were deflected from the true meridian as determined by observation on Polaris at eastern elongation. The distances were measured with 100-ft. and 500-ft. steel tapes.

#### REPORT.

The lode line of each location of this claim was run directly upon the ground, and the several corners established by means of offsets from the lode lines. All tie lines were run either directly upon the ground or by traverses, run upon the ground and submitted in a separate report herewith.

The S. E. Cor. Sec. 34, T. 28 S., R. 63 E., M.D.M., is a porphyry rock, 10x12x16 ins., set in a mound of rock, chiseled two notches E. and four notches W. This is the nearest standing corner of the public survey that can be found and identified.

Survey No. 2091, Diamond Wedge and Horse Shoe lodes.

All corners mentioned herein are pine posts, properly set and scribed with the number of the corner and survey. I find lines 4-5, 5-6 and 6-7, Diamond Wedge lode, to be N.42°31'E., N.58°51'W. 103.62 ft., and N.66°27'W. 752.36 ft., respectively, instead of N.47°39'E., N.57°35'W. 111.81 ft. and N.66°15'W. 754.42 ft., respectively, as approved. I also find line 4-5, Horseshoe lode,