No.25. A shaft, the center of which bears S 15°20'W 650 ft. from Cor.No.4, Hobo lode, 4 X 6 X 18 ft. deep, in solid rock.

Course S 2°E.

thwile discomment second event and to learned yeavalue and \$175.5%

No.26. Two trenches, the intersection of which bears S 38°W 276

ft. from Cor.No.4, Hobo lode, one, 4 ft. wide, 6 ft. deep,

running S 40°W 70 ft.; the second, 1.5 ft. wide, 2 ft.

deep, running S 58°30'E 150 ft.

Value \$200.

Other Improvements.

A ten-stamp amalgamation and concentration mill, the N.E. Cor. of which bears S 28°10'W 448 ft. from Cor.No.2, Cloro lode, 45 X 50 ft.. Course of long side S 83°30'W.

A wire rope, aerial tram, the southerly end of which bears S 36°45'W 546 ft. from Cor.No.2, Cloro lode, thence N 48°40'W 2025 ft. to the northerly end. Both belong to claimant herein subject to contract with construction companies.

aduction and selection in the selection of the selection

This survey was made with a C.L.Berger Mining Transit No. 3246. The courses were deflected from the true meridian as determined by an observation on Polaris at eastern elongation. The distances were measured with 100-ft. and 660-ft. steel tapes.

ALOS WOLL

Report.

The N. 1/4 Cor/Sec. 4, T.29 N, R.46 E, M.D.M. is a quartzite rock, 9 X 16 X 24 ins., with mound of rock surrounding and chisled with 1/4 on the north side.

The S. 1/4 Cor. Sec. 4, T. 29 N, R. 46 E, M. D. M. is a Quartz