

SURVEY NO. 4142

PINTO LODGE (continued)

S. 60°37' W., 257 ft., 5x7 ft., running S. 70° W., 78 ft.

to breast.

Value \$750.00

OTHER IMPROVEMENTS.

INSTRUMENT.

This survey was made with a C. L. Berger and Sons mining transit No. 7623. The courses were deflected from the true meridian as determined by direct solar observations. The distances were measured with a 600 ft. steel tape.

REPORT.

The lines of this survey and the connection to the corner of the public land survey were run either directly upon the ground or by traverses.

The SW. Cor. Sec. 16, T. 16 N., R. 63 E., Mt. Diablo B.

and M., is a limestone, 8x10 ins., 14 ins. long, in a mound of stone, chiseled 4 notches on the East and 3 notches on the South edges. This is the nearest standing

corner of the public land survey that can be found and

identified. The hub for the W. 1/4 Cor., Sec. 16, is a

stake, 2x2 ins., 6 ins. above ground, not marked.

Sur. No. 2971, Sentinel and Waverly Fraction lodes;

Corners 3 and 3 are pine posts, properly set and scribed with the number of the corner and survey. I find lines 3-4 and 3-4 to be correct as approved.

The SE. Cor. Jefferson Morefoot No. 2 lode, unsurveyed, is a pine post properly set and marked with the name of

the claim and corner. I find the South side line to be

N. 79° 33' 40" W., 1423.44 ft.

The SW. Cor. Sunday lode, unsurveyed is a pine post properly set and marked with the name of the claim and corner.

Note;-Any discrepancy between these field notes and the amended location certificate is due to errors in the latter.