

The dry-house, the S.W. corner of which bears from
 Cor. No. 4, Warrior Lode, N. 64° E. 215 ft., 14 x 18
 ft., course of long sides S. 66° E. All above improvements belong to the claimant herein.

INSTRUMENT.

This survey was made with a Lietz transit No. 1364,
 The courses were deflected from the true meridian, as
 determined by observation on Polaris at elongation, and
 checked with the true meridian as established by the
 U. S. G. S. The distances were measured with standard
 100-ft. and 660-ft. steel tapes.

REPORT.

All tie lines, and the lode line of each location
 were run directly upon the ground.
 The section corner to Sec's 1, 2, 35 and 36, T. 2
 N., R. 42 E., Mt. Diablo B. and M. is a porphyry
 rock, 15x12x10 ins., set on solid rock, chiseled one
 notch on East and five notches on West faces. This is
 the nearest standing corner of the Public survey to any
 corners of the locations of this survey. The 1/4
 section corners on the north and west boundaries
 respectively, of Sec. 1, T. 2 N., R. 42 E., Mt. Diablo
 B. and M. were found on the side of hills where their
 positions were unstable and unreliable.

The N.E. Cor. Sec. 1, T. 2 N., R. 42 E., Mt. Diablo
 B. and M., is a porphyry stone 18 ins. long, 12 ins.
 square, set on top of ground, chiseled six notches on
 N., S., and W. faces, surrounded by monuments of stone.
 Sur. No. 2061, Maggie O, Iroquois and Drummond
 Lodes: Corners 2-3 Maggie O and Iroquois, 2 Iroquois,
 2, 3 and 4 Drummond are pine posts, properly set and
 scribed with the number of the corner and survey.