

## Survey No. 4287.

## Other Improvements Contd.

thence N 36°-45'E 16.3 ft, thence S 54°-13'E 64.0 ft, thence to the place of beginning, Property of claimant herein.

## -- - Instrument.--

This survey was made with a F.E. Brandis 4½ ins limb transit graduated to 1' of arc, and a Buff and Buff 5" limb Engrs transit, graduated to half minutes.

The courses were deflected from the true meridian as determined by a direct Solar Observation. The distances were determined with a 66 ft steel Lufkin rule tape and a 564 ft steel tape, graduated to feet, the end foot marks graduated to tenths.

## ---- Report.---

The section corner common to Secs 28-29-32-33. Tp 28 N-R 34 E. M.D.B and M. 1. is a rhyolite stone diamond shaped 1.6 ft high 8 ins wide at base and 1" ~~in~~ on top marked four notches on East side, and one notch on South side; beside this stone in position, I drove a 7/8" iron rod in the ground, rod is round and 3 ft long.

1/4 Sec Cor between Secs 29 & 32 is a Rhyolite stone 12" x 12" ins square at base, and 24" ins high marked 1/4 S.. Top of rock is 2" x 12" by 24" high.

All of the other 1/4 Sec Corners were rhyolite rocks marked 1/4 on S faces.

The N.E. Cor and N side Center Cor and S.E. Cor of the Argente No. 1 lode unsurveyed are stone built up monuments, 4 ft high, 3 ft base, and marked by a small board with the name of the claim and corner placed on the board, and board placed on the rock monument..

The line between Cor to Secs, 28-29-32-33 Tp 28 N-R 34 E, M.D. B. and 1/4 Sec Cor between Secs 28-32. bears N 89°-47'-30"W, 2635.18 ft.