

SURVEY NO. 4302 A & B.

This survey was made with a C. L. Berger & Sons No. 4 transit. The courses were deflected from a meridian established in connection with my Survey No. 3340. The distances were measured with a Lufkin 660 ft. steel tape.

REPORT.

The N. E. Cor. Sec. 24, T. 14 N., R. 37 E., M. D.

M., is a stone 4 x 9 ins. showing 12 ins. above ground, marked with 3 notches on its north edge and 3 notches on its south edge. This is the nearest standing corner of the public survey that can be found and identified.

Cor. No. 1. Amethyst Extension lode unsurveyed is a stone 10 x 14 ins. showing 8 ins. above ground, chiseled 1A-4303.

Cor. No. 4 Amethyst Extension lode Sur. No. 3340 is a stone 8 x 14 ins. showing 10 ins. above ground, chiseled 4-3340.

The N. E. Cor. Sec. 12, T. 13 N., R. 37 E., M. D.

M., is a stone 5 x 9 ins. showing 8 ins. above ground, marked with 1 notch on its north edge and 5 notches on its south edge.

The oath of the chainman, Mr. Fred Cole, appearing herein as having been administered by myself is due to the fact that a disinterested Notary Public could not be reached by him without a great deal of inconvenience and expense.

Note: The disagreement between these field notes and the location certificates is due to errors in the latter.

OTHER IMPROVEMENTS.

None.

INSTRUMENT.