

OTHER IMPROVEMENTS.

None.

I N S T R U M E N T.

This survey was made with a Berger Mining Transit No.

6. The courses were deflected from a true meridian determined by direct solar observation. Distances were measured

with a 660 ft. steel tape.

R E P O R T .

The N.E. Cor. of Sec. 33, T. 8 N., R. 35 E. M.D.M. is a limestone boulder 6 x 12 x 18 ins. set in mound of stone and has three notches on the east and one notch on the south edge.

The $\frac{1}{4}$ Cor. between Secs. 33 & 34, T. 8 N., R. 35 E. M.D.M. is a limestone boulder 6 x 8 x 24 ins. set in a mound of stone and has $\frac{1}{4}$ chisled on the west face.

Sur. No. 38 Mayflower Lode.

The corners of this lode are 4 ins. square posts showing 3 feet above ground in mounds of earth and stone marked "U.S.S.No.38 Mayflower Mine" and the post number.

Sur. No. 40 Silver Guardian Lode

Corner No. 3 of this lode is a 4 ins. square post set in mound of earth and stone, showing three feet above ground marked "U.S.S.No.40 Silver Guardian Mine" Post No. 3".

Sur. No. 44 Turk Lode

Cor. No. 3 of this lode is a 4 ins. square post showing 3 ft. above ground in mound of earth and stone scribed TURK-3-44, having been renewed recently.

E R R O R S.

I find the following errors in the lines of prior surveys:--

U. S. Public Land Survey:-- The line between Secs.