

Other Improvements.

A cabin the S.E. corner of which bears from Cor. No. 1 Argo lode N $1^{\circ} 30' W$, 103 ft. 10 by 12 feet, course of long side east and west.

A cabin the N.E. corner of which bears from Cor. No. 1 Argo lode N $50^{\circ} 15' W$, 163 feet, 12 by 20 feet, course of long side N $28^{\circ} E$.

A hoist house, the S.E. corner of which bears from Cor. No. 1, Golden Fleece lode N $28^{\circ} 20' W$, 350 feet, 10 by 12 feet, course of long side N $30^{\circ} E$.

Instrument..

This survey was made with a C.L. Berger and Sons mining transit No. 3369.

The courses were deflected from the true meridian as determined by direct solar observations.

The distances were measured with 100 foot and 500 foot steel tapes.

Report.

The lode line of each location of this claim was run directly upon the ground, and the several corners established by means of offsets from the lode lines. All tie lines were run directly upon the ground.

The 1-4 sec. cor. between secs, 13 and 24, T 13 N, R 27 E, M.D. Base and Meridian is an eruptive stone 6 x 9 ins. by 7 ins. above ground, firmly set, with a mound of stone 2 foot base, 1 1-2 feet high N. of the cor. Chiseled 1 -4 on the N. face.

Note:

The discrepancies between the course and length of the several lode lines, each way from their respective discovery points, as given in the location certificates