

REPORT.

The lode line of each location of this claim was run either directly upon the ground or with intermediate points, and the several corners established by means of offsets. All tie lines were run either directly upon the ground or by traverses, run upon the ground and submitted in a separate report herewith.

The S.W. Cor. Sec. 21, T 39 N, R 46 E, M.D.M. is a rhyolite stone chiseled with 4 notches on the east side, 2 notches on the south side and a X on the top to designate the exact point, 6x12 ins. showing 14 ins. above the ground. This is the nearest standing corner of the public land survey that can be found and identified.

Missing link lode, unsurveyed.
Corners No. 1, 4 and 5 are pine posts properly set and marked. I find course of lines 4-5 and 5-1 to be S 7°38'W and S 88°59'W respectively.

Bonanza lode, unsurveyed.
Corners No. 1, 2 and 3 are pine posts properly set and marked. I find course of lines 1-2 and 2-3 to be N 3°E and S 79°07'E respectively.

Sur. No. 3738 Gold Town lode.

Corners No. 1 and 4 are pine posts properly scribed. Corner No. 4 is properly set. Corner No. 1 is loosely set in mound of earth and stone. From the top of Corner No. 1 as I found it Corner No. 4 bears N 12°08'W 593.3 ft.

From the S.W. Cor. Sec. 21, T 39 N, R 46 E, M.D.M., above described, a stone 4x5x7 ins. situated in the center of circle of small stones bears N 21°12'W 98.6 ft. This was pointed out to me as the true Section Cor. by an old resident of the district who was familiar with many of the corners in the district. No markings of any kind were found on any of the stones. Also at N 44°21'E 162.23 ft. was found a small survey peg, 1x1.5x12 ins. long, in center of a circle of small rocks 2.5 ft. in diam. none of