

Other Improvements (Continued)

A cut, the center of which bears from Cor. No. 1, Operator No. 3 Lode, N. 25° 50' W. - 318 ft., 4 by 10 ft., 4 ft. deep, course long sides N. 15° E.

A cut, the center of which bears from Cor. No. 1, Operator No. 3 Lode, N. 36° 40' W. - 320 ft., 5 by 10 ft., 5 ft. deep, course long sides N. 23° E.

Instrument.

This survey was made with an A. Lietz Light Mountain transit, No. 1640. The courses were deflected from the true meridian as determined by direct solar observations. The distances were measured with 100 ft. and 500 ft. steel tapes.

Report.

The lode line of each location of this claim was run directly on the ground, and the several corners established by means of offsets from the lode lines. All tie lines were run directly upon the ground.

The Northwest Cor. of Sec. 2, T. 1 N. R. 42 E. M. D. B. & M. is a stone, chiseled with 2 notches on the East face, and 4 notches on the West face. The Southeast corner of the abovementioned section is a stone, chiseled with 1 notch on the East face and 5 notches on the South face. These are the nearest standing corners to the respective locations that can be found and identified.

Sur. No. 4589, Rosetti No. 3 Lode:

Corners 1, 2, and 3, are pine posts, properly set and scribed with the number of the corner and survey. I find lines 1-2, and 2-3 to be correct as approved.

Note.- The discrepancies between these notes and the amended location certificates are due to errors in the latter.

Line 3-4, Hesitation Lode (Uns.) is S. 59° 43' W. - 560.7 ft.