## INSTRUMENT.

This survey was made with a Lietz Mining Transit No. 5262. The courses were deflected from the true meridian as determined by direct solar observations. The distances were measured with a 660-ft. steel tape.

## REPORT.

The S.W.Cor.Sec.35, T 2 N., R 42 E., M.D.M. is a rhyolite stone 6x8 ins. showing 10 ins. above ground and surrounded with other stones forming a small monument, marked with two notches on the east side and four notches on the west side and a cross chiseled on the top to mark the exact spot.

Sur. No. 4406 Operator No. 2 lode.

I find corners 1,2 and 3 to be pine posts properly set and scribed. I find courses of lines 1-2 and 2-3 to be correct as approved.

Sur.No.4409 Toggery Ex. No.2 lode.

I find corners 2-3 and 4 to be pine posts properly set and scribed, and courses of lines 2-3 and 3-4 to be correct as approved.

Hesitation lode, unsurveyed.

The east side center and the S.E.Cor. are pine posts 4 ins. square, showing three feet above ground with a few loose rock piles around the base. The S.W.Cor. is identical with Cor.No.3 Sur.No.4409 Toggery Ex.No.2 lode. It is faintly marked in lead pencil S.W.Cor.Hesitation. The S.E.Cor. is marked S.E.Cor.Hesitation and the east side center is marked E.S.Cen.Hesitation. No other corners were found. The course of the east side line as determined by the east side center and S.E.Cor. is N 32°02'W. The course and distance between the S.E. and S.W.Cors. is S 50°43'W 561. ft. The west side line was assumed to coincide with the east side line of Sur.No.4409 Toggery EX.No.2 lode.