

A frame house, the Northwest corner of which bears from the location monument, San Miguel No. 3 lode, S.11°47'W., 271 ft., 14 X 24 ft. Course of long sides S.79°E.

An ore bin and shoot, the Southeast corner of which bears from the location monument, San Miguel No. 3 lode, S.19°16'W., 204 ft., 14 X 21 X 10 ft. high. Course of long sides N.54°W.

A frame blacksmith shop, the Northeast corner of which bears from the location monument, San Miguel No. 3 lode, S.41°27'W., 134 ft., 12 X 16 ft. Course of long sides N.52°20'W. At the end is a shed, 11 X 13 ft.

A frame engine house, the Northwest corner of which bears from the location monument, San Miguel No. 3 lode, S.37°20'W., 131 ft., 16 X 47 ft. Course of long sides S.52°20'E.

The above described improvements all belong to the claimant herein.

Instrument.

This survey was made with a C. L. Berger & Sons. transit No. 4017. The courses were deflected from the true meridian as determined by direct solar observations. The distances were measured with 100-ft. and 300-ft. steel tapes.

Note:- The disagreements between these field notes and the location certificates are due to errors in the latter.

Report.

The $\frac{1}{4}$ Sec. Cor. between secs. 5 and 32, Tps. 29 and 30 N., R. 46 E., M. D. M., to which connection is herein given, is a red sandstone, showing 3 X 8 X 12 ins. above the ground in mound of stone, marked $\frac{1}{4}$ on North face and cross (X) on top. Connection is given to this corner for the reason that it is the nearest corner that could be identified.