

COMMON IMPROVEMENTS.

Improvement No. 5 of the Mormon Girl No. 1 lode, consisting of a 300 ft. vertical shaft and lateral workings is a common improvement for the benefit of each of the locations embraced in said mining claim and it is thru this shaft and its future workings and extensions that claimant will and can most economically develop all of said lodes. The bottom of said shaft is now approximately 220 ft. lower than the lowest part of the surface of any of the ground embraced in said claim. An undivided one-fifth interest of a total value of \$22,800.00 is therefore credited to each of said lodes.

OTHER IMPROVEMENTS.

A corrugated iron shaft house, the S.E. Cor. of which bears from the discovery monument of the Mormon Girl No. 1 lode, N. 86° 31' W. 143.7 ft. 20 by 30 ft. Course long side N. 31° 40' E. Claimant herein.

INSTRUMENT.

This survey was made with an Ainsworth Light Mountain Theodolite Transit. The courses were deflected from true meridian as determined from direct solar observations. The distances were measured with 650 ft. and 100 ft. steel tapes.

REPORT.

The lode line of each location of this claim was run directly upon the ground and the several corners established by means of off-sets from the lode lines. All tie lines were run directly upon the ground or figured thru the lines of this survey.

The North $\frac{1}{4}$ Section Corner, Section 34, T. 2 N., R. 42 E., M.D.M., is marked by a light colored rhyolite stone showing 10 ins. above a mound of stone and earth, chiseled " $\frac{1}{4}$ " on the North face.

Survey No. 4109, Burger, Monte Christo and Eureka lodes:- All corners mentioned herein are stone corners, with a mound of stone and earth alongside and chiseled as approved.