

improvement No. 4, course of long sides N.  $50^{\circ}$  E.

Value \$200.00

No. 6. An open cut, the center of the face of which bears from Cor. No. 4, S.  $9^{\circ} 45'$  W., 84 ft., 10 ft. high, 5 ft. wide, running S.  $27^{\circ}$  W., 15 ft. to toe. From the face of the cut a tunnel, 4x7 ft., runs N.  $27^{\circ}$  E., 20 ft. to center of raise, 5x5 ft., 20 ft. high to surface. At the face of the cut is a shaft, 4x6 ft., 10 ft. deep.

Value of cut, tunnel, raise and shaft. \$900.00

No. 7. A shaft, the center of which bears from Cor. No. 4, S.  $0^{\circ} 55'$  E., 62 ft., 6x6 ft., 18 ft. deep, course of sides N.  $27^{\circ}$  E., from the bottom of which a drift, 5x8 ft., runs N.  $27^{\circ}$  E., 20 ft. to face.

Value of shaft and drift. \$500.00

#### OTHER IMPROVEMENTS.

None.

#### INSTRUMENT.

This survey was made with a Buff and Buff, Model 25 transit, No. 10482. The courses were deflected from the true meridian as determined by direct solar observations.

The distances were measured with a 500-ft. steel tape.

#### R E P O R T

The boundaries of the lode of this claim were run directly upon the ground.

All tie lines were run by traverses run upon the ground.

The  $\frac{1}{2}$  Cor. on the E. boundary of Sec. 10, T. 26 N., R. 52 E., M.D.B. & M., is a sandstone rock, 5x16 ins., extending 10 ins. above a mound of stone and properly chiseled. This is the nearest standing corner of the Public Survey that can be found and identified.

Red Jacket Consolidated Lode:

All corners and the South end line stake of the location were pine posts, 4 ins. in diameter, properly set and marked.

The differences between these notes and the courses