

SURVEY NO. 4473.

5.

FINAL OATHS FOR SURVEYS

REPORT.

The boundaries of the lode of this claim were run directly upon the ground. All tie lines were run by traverses, run upon the ground.

The E. $\frac{1}{4}$ Cor. of Section 10, T. 26 N., R. 52 E., M. D. B. & M., is a sandstone rock, 5x16 ins., extending 10 ins. above a mound of stone, chiseled $\frac{1}{4}$ on the E. and W. faces. This is the nearest standing corner of the public survey that can be found and identified.

Sur. No. 40, Mc Coy Lode:

Cor. No. 1 is a pine post 4 ins. square, properly set and marked with the number of the corner and survey and the name of the lode.

I find Cor. No. 1 to be N $66^{\circ} 40' 43''$ W., 4294.19 ft., from the East $\frac{1}{4}$ Cor. of Sec. 10, T. 26 N., R. 52 E., M.D.B. & M., instead of S. $58^{\circ} 45'$ E., 1690 ft., from the N. W. Cor. of said Section as approved.

Water Pipe Lode: Mineral Surveyor, in marking the corners and surveying

All corners and the side line stakes were pine posts 4 ins. in diameter, properly set and marked.

The differences between these notes and the courses and distances in the location certificate are due to errors in the latter.

Note:

Intersections with the Section line between Secs. 3 and 10, T. 26 N., R. 52 E., M.D.B. & M., are calculations using the official records of the Public Land Survey.

Subscribed and sworn to by the above-named persons before me this 13th

day of October, 1920.

NOTARY PUBLIC COUNTY OF ELKO,
STATE OF NEVADA.