

FINAL OATHS FOR SURVEYS.

10 ft. 4 X 6 ft. 25 ft. deep, timbered 10 ft.

Value \$500.00

Other Improvements

None.

Instrument

This survey was made with an Ainsworth transit.

The courses were deflected from the true meridian as determined by direct solar observations.

The distances were measured with 100 ft. and 600 ft. steel tapes.

Report.

FINAL OATHS OF ASSISTANTS.

The lode line of the High Grade lode was run directly upon the ground, and the several corners established by means of offsets from the lode line.

The tie from Cor. No. 1 to the S. E. Cor. Sec. 25, was run direct upon the ground. The courses of the boundaries of Sections 25 and 36 T. 25 N. R. 24 E. and Sections 30 and 31 T. 25 N. R. 25 E. M.D.B & M. were determined direct upon the ground.

The S. W. Cor., Sec. 25, is a stone 18 X 8 X 6 in. chiseled with one notch on south face and one notch on east face.

The S. E. Cor., Sec. 25, T. 25 N. R. 24 E. is an iron post, 3 in. in diameter, 1 ft. above ground, marked T. 25 N. R. 24 E. S 25, S 36., R. 25. E. S 30, S 31.

The E. $\frac{1}{4}$ Cor. Sec. 25 is an iron post 1 in. in diameter, marked $\frac{1}{4}$.

The S. $\frac{1}{4}$ Cor. Sec. 30, is an iron post 1 in. in diameter, marked $\frac{1}{4}$.

The S. E. Cor. Sec. 36, T. 25, N. R. 25 E. is an iron post, 1 ft. above ground, 3 in. in diameter, marked T. 25 N.R. 24 E. S 36., R. 25 E. S 31.,