

FINAL OATHS FOR SURVEYS.

OTHER IMPROVEMENTS.

A frame house, the SW. corner of which bears from Cor. No. 1, Baltimore lode, S. 73° 14' E., 819.6 ft., 12 x 28 ft., course of long sides N 37° W.

A tie shed, the SW. corner of which bears from Cor. No. 1, Baltimore lode, S. 78° 36' E., 737.5 ft., 12 x 15 ft., course of long sides, N. 54° E.

A planked loading platform, the SE. corner of which bears from Cor. No. 1, Baltimore lode, S. 67° 46' E., 645 ft., 16 x 74 ft., course of long sides S. 48° W.

INSTRUMENT.

This survey was made with a Buff and Buff, Model 25 transit, No. 10482. The courses were deflected from the true meridian as determined by direct solar observations. The distances were measured with a 500-ft. steel tape.

REPORT.

The lode line of each location of this claim was run directly upon the ground, and the several corners established by means of offsets from the lode lines. All tie lines were run either directly upon the ground or by traverses, run upon the ground.

The NW. corner of Sec 18, T. 33 N., R. 53 E., M. D. B. & M., is a willow stake, set in a mound of earth and stone and properly scribed. The South 1/4 corner of Sec. 7, T. 33 N., R. 53 E., M. D. B. & M., is a pine post set in a mound of earth, witnessed by pits, scribed 1/8 on the North face. These are the nearest standing corners of the public survey that can be found and identified.

I find the South line of Sec. 7, T. 33 N., R. 53 E., M. D. B. & M., to run from the SW. corner of said Section N. 89° 13' 10" E., 2540.2 ft. to the South 1/4 corner of said Section, instead of East, 2527.8 ft. as approved.