

A frame transformer house the west corner of which bears N 45°E 300 ft. from Cor.No.3 Apex No.6 lode.

8x12 ft. Course of long side N 45°E.

A frame blacksmith shop the south corner of which bears N 28°E 200 ft. from Cor.No.3 Apex No.6 lode. 14x14 ft.

Course one side N 45°W.

A galvanized iron machine shop the south Cor. of which bears N 10°E 225 ft. from Cor.No.3 Apex No.6 lode.

12x20 ft. Course long side N 45°W.

A frame boarding house the S.E.Cor. of which bears

N 25°W 145 ft. from Cor.No.3 Apex No.6 lode. 16x34 ft.

with an "L" on the N.E.Cor. 10x12 ft. Course long side N 80°W.

A frame bunk house the S.E.Cor. of which bears N 25°W 380 ft. from Cor.No.3 Apex No.6 lode. 10x45 ft. Course of long side N 65°W.

A heavy timbered powder house the N.E.Cor. of which bears N 60°W 90 ft. from Cor.No.4 Apex No.6 lode, 8x10 ft. placed well within an open cut and practically covered with sand.

---

#### INSTRUMENT.

This survey was made with a Lietz Mining transit, No. 5262. The courses were deflected from the true meridian as determined by direct solar observations. The distances were measured with a 25 ft. and 660 ft. steel tapes.

---

#### REPORT.

The S.E.Cor.Sec.16 T 2 N., R 42 E., M.D.M. is a rhyolite stone 10x12x26 ins. set in mound of stone and scribed with three notches on the east and south sides respectively.

The E 1/4 Cor.Sec.16 T 2 N., R 42 E., M.D.M. is a