

ery monument S.59°07'E. 186.8 ft., 4 ft. wide, running S.55°E. 18 ft. to 8 ft. face. In solid rock.

Value, \$100.00

OTHER IMPROVEMENTS.

There are no other improvements on this claim.

INSTRUMENT.

This survey was made with a C.L.Berger & Sons' light mining transit No. 4370. The courses were deflected from the true meridian as determined by observation on Polaris at western elongation. The distances were measured with 100-ft. and 500-ft. steel tapes.

REPORT.

The lode line of this claim was run directly upon the ground and the several corners established by means of offsets from the lode line. All tie lines were run either directly upon the ground or by traverses, run upon the ground and submitted in a separate report herewith.

The S. 1/2 Cor. Sec. 2, T. 26 S., R. 64 E., M.D.M., is a quartz rock 9x16 ins., standing 12 ins. above the ground, chiseled 1/2 on the N. face. This is the nearest standing corner of the public survey that can be found and identified.

Although repeated search has been made by me for the S.W.Cor. Sec. 2, not only in connection with this survey but also in connection with other surveys executed by me in this vicinity (particularly Surs. Nos. 3684, 3847, 3873A and B, and others), it has never been found, and positively does not exist at the point described in the approved field notes of Am. Sur. No. 2085, Piatt lode, and in the approved field notes of Sur. No. 2351, Buster lode.

The S. 1/2 Cor. Sec. 3 has also eluded all search thus