

OTHER IMPROVEMENTS

None

INSTRUMENTS

This survey was made with a Lietz No. 5

Transit; the courses were deflected from the true

Meridian as determined by direct solar observations.

The distances were measured with 100 ft. and 660 ft.

Lufkin steel tapes.

Note: The disagreements between these field

notes and the location certificate of the South

Fraction lode with regard to the position of the

discovery monument and the courses and distances

of the boundary lines are due to error in the latter.

REPORT

All lines of the South Fraction lode, and

the respective ties to Sec. Cors. 2, 3, 34, 35, Tps.

2 and 3 N., R. 42 E., M. D. B. & M., were made direct

upon the ground.

Cor. to Secs. 2, 3, 34 and 35, Tps. 2 and 3

N., R. 42 E., M. D. B. & M. is a granite stone 15 x

13 x 10 ins., with mound of stone, marked with 2 and

4 notches on the east and west sides respectively.

This corner agrees with its location, as determined

from the official record of Sur. No. 2386 Crocker lode.

The $\frac{1}{4}$ Sec. Cor. on the W. bdry. Sec. 2, T. 2

N., R. 42 E., M. D. B. & M., is a stone 16 x 10 x 5

ins. marked $\frac{1}{4}$ with mound of stone alongside. This

corner agrees with its location as determined from

the official record of Sur. No. 2386, Crocker lode.

Cor. No. 7, Sur. No. 2386, Crocker lode is

a porphyry rock 10 x 4 in. showing 12 ins. above

ground marked x-7-2386 and T-9-4469.