

OTHER IMPROVEMENTS.

There are no other improvements on the property.

INSTRUMENT.

The survey was executed with a Leupold & Voelpel Transit No. 177. Courses were determined by deflection from a meridian, determined by direct solar observations. The distances were measured with a 300 ft. steel tape.

REPORT.

All side centers are mounds of stone, 4 ft. base, and 3 ft. high.

The Corner of sections 2,3,34 & 35, Tps. 22 & 23 S., R. 63 E., is a pine post, 4 ft. long, 4 ins. square firmly set in a mound of stone with a stone, 20 ins. long, 10 ins. wide and 6 ins thick marked with 4 notches on one side and two notches on the opposite side, lying at the foot of the post.

The 1/4 corner between sections 2 & 3 is a stone, 18 X 10 X 8 ins., set in a mound of stone, and marked 1/4 on the west face. North half of section line between sections 2 & 3 I find to be N 2°49'E., 2806.14 ft. Diligent search failed to locate any trace of the 1/4 sec. cor., and the Sec. cor. west of the cor. of secs. 2,3,34 & 35, therefore intersections are computed from course given in the original field notes of the survey.

All lines of the claim and all tie lines were run directly on the ground.

This claim is surrounded on all four sides by Public Domain.

The differences between the location notices and this survey are due to the error in the former.

All the location corners of this claim were pine posts, firmly set and properly marked.

Las Vegas, Nevada.
November 16, 1921

Fred W. Rodolf
U.S. Mineral Surveyor.