

INSTRUMENT.

This survey was made with an Ainsworth Light Mountain Theodolite Transit. The courses were deflected from true meridian as determined from direct solar observations. The distances were measured with 100 ft. and 500 ft. steel tapes.

REPORT.

The lode line of each location of this claim was run directly upon the ground and the several corners established by means of off-sets from the lode lines. All tie lines were run directly upon the ground or figured thru the lines of this survey.

The N. $\frac{1}{4}$ Sec. Cor. Sec. 17, T. 25 S., R. 58 E., M.D.M., is marked by a limestone, 12x4 ins., showing 10 ins. above a mound of stone and earth, chiseled " $\frac{1}{4}$ " on the north face. This corner was found by me in making Survey No.4441 and the check for this corner is fully reported in the notes of that survey. Diligent search was made for a corner of the public survey nearer this claim but none could be found or identified.

Survey No.1854, Full Moon lode :-

All corners mentioned herein are juniper stakes, 3 ins. in diameter, set in mounds of stone and earth and scribed as approved. Diligent search was made for Corner No.3 of this lode but it could not be found. I find this claim to be in Section 16, T. 25 S., R. 58 E., M.D.M., instead of in Sections 20 & 21, T. 25 S., R. 58 E., M.D.M., as approved.

Survey No.4441, Producer lode :-

All corners mentioned herein are pine posts 4 ins. square, properly set and scribed as approved.

Note :-

All discrepancies between these notes and the amended certificates of location of the various lodes embraced in said mining claim are due to errors in said certificates.