

SURVEY NO. 4542. Continued.

7.

lode, N. 40° 15' E. 568 ft., 6 x 8 ft., 56 ft. deep,
timbered.

Value \$ 840.00

No. 3

A shaft which bears from Cor. No. 3, Boston
lode, N. 74° 30' E. 188 ft., 5 x 7 ft., 10 ft. deep.

Value \$ 100.00

No. 4

A shaft which bears from Cor. No. 3, Boston
lode, N. 88° 25' E. 135 ft., $3\frac{1}{2}$ x 6 ft., 5 ft. deep.

Value \$ 30.00

OTHER IMPROVEMENTS.

There are no other improvements.

INSTRUMENT.

This survey was made with a W. and L. E.
Gurley light mountain transit. The courses were deflected
from the true meridian, as determined by direct solar
observation. The distances were measured with 100 ft.
and 300 ft. steel tapes.

REPORT.

The lode lines of each location of this claim
was run directly upon the ground, and the several corners
established by means of off sets from the lode lines.
All tie lines were run either directly upon the ground
or by traverses, run upon the ground and submitted in
a separate report herewith.

The NE. corner of section 12, T. 13 N., R. 27
E., M.D.B. and M. is a stone 6 x 6 ins., 5 ins. above
the ground, with one notch on north face and 5 notches
on south face, with a cross chiseled on top, and with
mound of stone west of corner.

Sur. No. 3981, Capatola lode;

Corners 1, 2 and 3 are pine posts, properly
set and scribed with the number of the corner and survey.
I find line 1-2 to be correct as approved.

Sur