

Report.

S, W, Cor. Sec. 31, T 3 N., R 43 E., M.D.B and M, is a stone, 12X12X20 ins. above mound of stone, chiselled with six notches on the north, east, south and west faces, respectively.

After making a diligent search I was unable to find either of the 1/4 Sec. Cors. on the east and south boundaries, respectively, of Sec. 31, T 3 N., R 43 E., M.D.B and M.

All corners of Sur. No. 4190, Gold Finch and Gold Pheasant lodes are posts properly scribed with the initial of the claim, corner and survey number.
 Corner No. 1, Tonopah Bullion lode and Cor. No. 2, Florence lode, both of Sur. No. 3707, is a stone, chiselled, F-2, T.B-1-3707.
 Cor. No. 2, Sur. No. 3978, Eagle No. 5 lode, is a stone, chiselled E No. 5-2-3978.

As Cor. No. 1, Sur. No. 3707, Florence lode was destroyed, I assumed the course of line 1-2, for said lode to be N 65° 38' E., 600.0 ft.
 Owing to the fact that the surface ground within the lines of all the lodes of this claim has recently been visited by a heavy fall of snow, accompanied by high winds, all the improvements have been filled with snow to the extent of making it impossible to either locate or to make measurements at this time. The location of these improvements together with measurements and estimates of value will be embodied in a "Supplemental Report" which I will submit to your officer at a later date.

Tie from Cor. No. 1, Sur. No. 3707, Tonopah Bullion lode is S 78° 40' W., 2843.1 ft. instead of S 78° 46' W., 2842.0 ft. as approved.

This survey was made with a surveying instrument were deflected from the true meridian as determined by direct solar observations. Distances were measured with

100 ft. and 500 ft. steel tapes.