

A frame house, the northeast corner of which bears from Cor. No. 1, S. $29^{\circ} 58'$ W., 233 ft., 12 x 14.2 ft., course of long sides N. 57° E., claimant herein.

A frame house, the northeast corner of which bears from Cor. No. 1, S. $19^{\circ} 19'$ W., 246.5 ft., 12 x 26.6 ft., course of long sides, N. 58° E., claimant herein.

A frame house, the northwest corner of which bears from Cor. No. 6, N. 80° E., 356 ft., 22.2 x 24.3 ft., course of long sides N. $55^{\circ} 30'$ E., claimant herein.

A frame garage, the northeast corner of which bears from Cor. No. 6, N. 80° E., 356 ft., 12 x 14.2 ft., course of long sides S. $34^{\circ} 30'$ E., claimant herein.

INSTRUMENT.

This survey was made with a Buff & Buff, Model 25 transit, No. 10482. The courses were deflected from the true meridian as determined by direct solar observations. The distances were measured with 500-ft. and 5-ft. steel tapes.

REPORT.

The boundary lines of the location of this claim were run upon the ground. The tie line to the section corner was by traverse, run upon the ground. All other tie lines were run directly upon the ground.

The northeast corner of Sec. 9, T. 28 N., R. 47 E., M. D. M., is a quartzite rock, 6 x 10 ins. 10 ins. out of the ground, surrounded by mound of stone, chiseled with 3 notches on the east face and 5 notches on the south. This is the nearest standing corner of the public land surveys that can be found and identified.

Sur. No. 3086, Rough and Ready No. 1 lode:-

I find line 3-4 to be S. $54^{\circ} 50'$ W., 599.3 ft. instead of S. $54^{\circ} 54'$ W., 599.4 ft. as approved. I find Cor. No. 3 to be S. $46^{\circ} 42'$ W., 2600.2 ft. instead of Cor. No. 1 S. $77^{\circ} 32'$ W., 2919 ft. from the northeast corner of Sec. 9, T. 28 N., R. 47 E., M. D. M., as approved.