

Survey No. 4655.

Segregated Sub. No. 2 of the Alunite Lode Extended.

Other improvements.

A pit, 3x8 ft. 6 in. deep, in rock, bearing from Cor. No. 4 N. 22° 48' E. 759.7 ft., claimed by claimant herein.

A trench, partly cased, averaging 4 ft. wide, 5 ft. deep, 73.7 ft. long, the South end of which bears from Cor. No. 1, N. 21° 46' E. 495.2 ft., and running thence on average Course N. 3° 53' E. 73.7 ft. to North end thereof; claimed by claimant herein.

Instrument.

This survey was made with a Gurley light Mountain transit. The courses were deflected from the true meridians as determined by direct solar observations.

The distances were measured with 300 ft. steel tape.

Report.

The Corner of Sections 35 and 36 on South Boundary of Township No. 35 N. Range No. 29 E. of the M. D. Base M. is an iron post, 2 ins. diam., showing 2 ft. above ground in mound of stone, marked as *Cor. Cap T. 35 N., R. 29 E., S. 35 - S. 36.*

The U. S. Section Monument No. 293 is a sawed fir post, 7.5 x 8 ins., showing 5 ft. above the ground, in mound of rocks, marked U. S. L. M. 293.

Sur. No. 4355, Steel Suppler Mine No. 1, Place 1. Cor. No. 3 is a sawed pine post, 4 ins. square, showing 2.5 ft. above ground, in mound of earth and stone, marked 3-2-4355, S. 1 - S. 3.

Sur. No. 4620, Alunite Lode. Cor. No. 1 is a sawed pine post, 4 ins. square,