

FINAL OATHS FOR SURVEYS

Mineral Survey 4698

LIST OF NAMES

All of the above described improvements belong to claimant herein.

INSTRUMENT

This survey was made with a C.L. Berger and Sons No. 2 Transit. The courses were deflected from the true meridian as determined by direct solar observations.

The distances were measured with 100 and 500 ft. steel tapes.

REPORT

All lines and ties in this survey were run on the ground ~~and the ground~~ and the courses and distances found to be as herein given.

The S.E. Cor. of Sec. 36 T. 1 N. R. 33 E. M.D.M. to which connection is given, is a granite rock showing 8 x 10 x 12 inches above a mound of earth and stone, properly marked, with a monument of stone 3 ft. high alongside. Also a pine post to which is nailed an iron plate marked for a corner of the Inyo National Forest.

This was the nearest corner of the public survey that could be found and identified.

A diligent search was made for the S. 1/4 Sec. Cor. and the S.W. Cor. of Sec. 36 T. 1 N. R. 33 E. M.D.M. but no evidence of said corners could be found.

NOTE:

The disagreement between these field notes and the amended location certificates are due to errors in the latter.

Subscribed and sworn to by the above-named persons before me this

day of

November 1924

[Handwritten signature]

NOTARY PUBLIC