

A frame building, the NE. corner of which bears from
 Cor. No. 2 N. 48° 07' W., 53.4 ft., 20.3 x 30.2 feet,
 course of long sides N. 1° 40' E., claimant unknown.

A frame building, the SE. corner of which bears from
 Cor. No. 2 N. 48° 07' W., 53.4 feet, 30.2 x 41 feet,
 course of long sides, N. 88° 20' W., claimant unknown.

A tie building, the SE. corner of which bears from
 Cor. No. 2 N. 74° 49' W., 139.3 ft., 16.1 x 24.1 ft.,
 course of long sides, S. 1° W., claimant unknown.

INSTRUMENT.

This survey was made with a Buff & Buff, Model 25
 transit, No. 10482. The courses were deflected from
 the true meridian as determined by direct solar obser-
 vations. The distances were measured with a 500 foot
 steel tape.

REPORT.

The boundaries of this location were run upon the
 ground. All tie lines were run directly upon the ground.

Monument 12.50 chains South on 42nd. mile of the
 Nevada-Utah State line, is a limestone rock, 6 x 8 ins.,
 chiseled (X), 8 ins. out of a mound of earth and stone,
 situate on a limestone ridge. This is the nearest

corner of the public land surveys. The SW. corner of Sec. 18, T. 1 S., R. 19 W., S. L.
 B. & M., is a limestone rock, 6 x 10 ins., 13 ins.
 above ground with mounds of stone alongside, chiseled
 3 notches on the north side and 3 notches on the south
 side, CC, U on the east side and N on the west side. I
 find it to be 36.6 ft. N. 0° 15' E., from the above
 described State boundary line monument.

Salt Spring Number Two lode:-

All corners were pine posts properly set and
 marked with the name of the lode and corner. The lo-
 cation certificate fails to give a tie to a corner of