

OTHER IMPROVEMENTS

A frame blacksmith shop covered with corrugated iron the southwest corner of which bears S.85°40'W 350 ft. from the Disc. Point of Betty O'Neal No.2 Lode. Size of shop, 12 x 14 ft. Course of long sides N.49°30'E.

A frame cook house 12 x 20 ft., the southwest corner of which bears N.75°00'E. 50 ft from Cor.No.4, Betty O'Neal Mill Site. Course of long sides S.60°00'E.

INSTRUMENT

This survey was made with a W. & L. E. Gurley Light Mountain Transit No. (None given). The courses were deflected from the true meridian as determined by observation on Polaris at western elongation. The distances were measured with a 100 ft. steel tape.

REPORT.

The Lode Lines of each location of this claim was run directly upon the ground and the several corners established by means of offsets from the Lode Lines.

All ties lines were run either directly or by traverses on the ground.

The N.W. Cor. Sec. 35, T12N. R36E., M.D.E. & M. is a mound of stone and a U.S. Forest Service post set therein for a forest reservation corner. It is taken as the true location of the government corner by the U.S. Forest Service and checks as to topography in the field notes on file in the Public Survey Office.

This is the nearest standing corner of the public survey that can be found and identified.

The corners of Greenstone Lode, unsurveyed, are rock monuments.

The corners of Gloria No. 5 Lode, unsurveyed, are pine posts.

EXPENDITURE OF FIFTY HUNDRED DOLLARS.

I certify that the value of the labor and improve- ments made upon the claim for the benefit of each of the loca- tions embraced in said claim by claimant and that a statement in not less than five hundred dollars and that for recovery of said claimant's costs and expenses in the amount of \$500.00.