

SURVEY NO. 4841

EXPENDITURES

No report of expenditures returned at this time.

OTHER CORNER DESCRIPTIONS AND SUPPLEMENTAL DATA

The corner of secs. 26, 27, 34 and 35, T. 34 N., R. 34 E., M.D.M., was found to be a $1\frac{1}{2}$ ins. diam. drill rod, flush with the surface of the ground, firmly set in a drilled hole in a rock outcropping. This location was pointed out by official of the company and substantiated by reduplication of ties from prior location corners shown on a map of a survey by John Runner, C.E. now in the files of the Nevada Massachusetts Company at Tungsten, Nevada, and taken as the best evidence of the original position of the corner.

Set an iron post, 2 ins. diam., 3 ft. long, with flared base, with the top flush with the surface. The post was set in concrete. The 2 inch square brass cap was marked COR SECS 26-27-34-35-T34N R34E SUR 4841. (There was insufficient room to stamp the corner number and initial of the claim name on the brass cap).

The $\frac{1}{4}$ sec. corner of secs. 26 & 35 is marked by a Volcanic stone, 15x12x8 inches, set 10 ins. in the ground, marked $\frac{1}{4}$ on the W. face.

The $\frac{1}{4}$ sec. corner of secs. 26 & 27 is marked by a Volcanic stone, 20x15x10 ins., set in a mound of stone, and marked $\frac{1}{4}$ on the W. face.

The corner of secs. 25, 26, 35 & 36, T. 34 N., R. 34 E., M.D.M., is a stone, properly marked, firmly set, and in a mound of stone.

The line between the corner of secs. 26, 27, 34 & 35 and the $\frac{1}{4}$ cor. between secs. 26 & 35, T. 34 N., R. 34 E., M.D.M. was found to be S. 89°58' W., 2667.6 ft. instead of S. 89°55' W., 2636.7 ft. as approved.

The line between the $\frac{1}{4}$ corner of secs. 26 and 35 and the corner of secs. 25, 26, 35 & 36, T. 34 N., R. 34 E., M.D.M. was found to be S. 89°51' W., 2670.8 ft. instead of S. 89°55' W., 2636.7 ft. as approved.

The line between the corner of secs. 26, 27, 34 and 35 and the $\frac{1}{4}$ corner of secs. 26 and 27, T. 34 N., R. 34 E., M.D.M. was found to be N. 0°01' E., 2648.2 ft. instead of N. 0°01' W., 2640 ft. as approved.

FIELD ASSISTANTS

Name	Capacity
Gail Gladding	Chainman