Mineral Survey 4926 A

SHARON LODE

At Cor. No. 1 of the Sharon lode, identical with Cor. No. 1 of the Cammy lode of this survey.

Set an iron post, 24 ins. long, 2 ins. diam., 19 ins. in the ground, with 3 ins. diam. brass cap mkd. S-1 C-1 4926 A; from which

The cor. secs. 4 and 5, T. 28 N., R. 44 E., and secs. 32 and 33, T. 29 N., R. 44 E., Mt. Diablo Mer., bears N. $6^{\circ}57'06''$ W., 10949.77 ft. dist.; monumented with an iron post $2\frac{1}{2}$ ins. diam., 6 ins. above ground, firmly set, with brass cap properly marked and dated 1968; a steel fence post is set 1 ft. N. of Cor.

U.S.L.M. 4877 bears N. $60^{\circ}26'44"$ E., 1335.73 ft. dist,; monumented by a 6 ins. diam. concrete post, 18 ins. above ground, firmly set, with a punch mark in the center of a 1964 penny at top; a mound of rock $3\frac{1}{2}$ ft. diam., 2 ft. high, E. of cor.

Cor. No. 1, M.S. No. 4877 Mustang lode, bears N. 27°47'29" E., 1538.77 ft. dist,; monumented by a 2 ins. diam. iron post, 30 ins. above ground, firmly set, with a 2 ins. x 6 ins. copper plate properly marked

Cor. No. 4, M.S. No. 4877 Mustang lode, bears S. $77^{\circ}17'14''$ E., 611.08 ft. dist,; monumented by a 2 ins. diam. iron post, 30 ins. above ground, firmly set, with a 2 ins. x 6 ins. copper plate properly marked.

Cor. No. 4, IMCO NO. 24 Millsite Claim millsite of this survey, bears N. $9^{\circ}59'07''$ W., 5595.59 ft. dist.; hereafter described.

No local bearing objects or bearing trees available.

Thence N. 89°03'36" E.

Center of road, bears N. 70° W. and S. 55° E.

Center of road, bears N. 21° W. and S. 18° E.

Lode line; discovery point bears S. 01°31'19" W., 100.0 ft. dist.

325 | Center of small wash, course North.

80

170

300

GPO 839-785