

Mineral Survey No. 4941

FEET	
	<p style="text-align: center;">H. AND L. #1 MINE LODE</p> <p>At Cor. No. 1 of the H. and L. #1 MINE lode.</p> <p>Set an iron post, 24 ins. long, 1½ ins. diam., 19 ins. in the ground, surrounded by a rock mound, 24 ins. diam., 5 ins. high, with a brass cap mkd. H&L1-1-4941; from which</p> <p style="padding-left: 40px;">The NE cor. of sec. 24, T. 31 N., R. 46 E., Mt. Diablo Mer., bears N. 30°49'26" E., 2,885.11 ft. dist., monumented by a drill steel, 1 in. diam., 4 ins. above ground, surrounded by a rock mound, 25 ins. diam., 5 ins. high, with steel fence post.</p> <p style="padding-left: 40px;">The SW cor. of sec. 18, T. 31 N., R. 47 E., Mt. Diablo Mer., bears N. 32°48'17" E., 2,742.23 ft. dist., monumented by a rock in a rock mound, 22 x 29 ins., 7 ins. high, with steel fence post in center.</p> <p>No local bearing trees or bearing objects available.</p> <p style="text-align: center;">Thence N. 18°19'39" E.</p>
118.	Center of cut, bears N. 85° W. and S. 85° E.
210.	Center of road, 20 ft. wide, bears N. 30° W. and S. 30° E.
330.	Center of road, 25 ft. wide, bears N. 36° W. and S. 58° E.
360.	Edge of extensive trenching, bears S. 69°57' E.
405.	Top of ridge, bears N. 83° E. and S. 83° W.
456.	Edge of extensive trenching, bears N. 34°30' E.
1350.	Center of wash, course S. 84° W.
1493.44	<p>Cor. No. 2.</p> <p>Set an iron post, 24 ins. long, 1½ ins. diam., 11 ins. in the ground, surrounded by a rock mound, 27 ins. diam., 12 ins. high, with a brass cap mkd. H&L1-2-4941; from which</p> <p style="text-align: center;">Thence S. 46°04'35" E.</p>