

Mineral Survey No. 4945

FEET	
	BEACON #1 MINE LODE At Cor. No. 1 of the BEACON #1 MINE lode, identical with Cor. No. 1 of the Beacon Extension No. 2 lode of this survey. Set an iron post, 24 ins. long, 2 ins. diam., 18 ins. in the ground, with a brass cap mkd. B1-1-BE-2-4945; from which The SW cor. of sec. 18, T. 31 N., R. 47 E., Mt. Diablo Mer., bears S. 39°08'54" W., 1,663.78 ft. dist., monumented by a rock in a rock mound, 22 x 29 ins., 7 ins. high, with steel fence post in center. The NE cor. of sec. 24, T. 31 N., R. 46 E., Mt. Diablo Mer., bears S. 43°25'24" W., 1,538.78 ft. dist., monumented by a drill steel, 1 in. diam., 4 ins. above ground, surrounded by a rock mound, 25 ins. diam., 5 ins. high, with a steel fence post. No local bearing trees or bearing objects available. Thence S. 43°26'27" W.
60.	Center of wash, course N. 83° W.
80.	Center of road, 10 ft. wide, bears N. 10° E. and S. 37° E.
100.	Enter parking area, edge bears N. 75° W. and S. 5° E.
250.	Leave parking area, edge bears East and West.
340.	Center of road, 15 ft. wide, bears N. 71° E. and S. 71° W.
400.	Enter tailings pile, edge bears N. 71° E. and S. 71° E.
975.	Center of wash, course N. 52° W.
1060.	Leave tailings pile, edge bears N. 50° W. and S. 50° E.