FEET

## CAROL #1 LODE

At Cor. No. 1 of the Carol #1 lode, identical with Cor. No. 1 of the Carol #2 lode of this survey.

Set an iron post, 24 ins. long, 2 ins. diam., 19 ins. in the ground, with a brass cap mkd. C1-1-C2-1-4949; from which

The cor. of secs. 27, 28, 33, 34, T. 28 N., R. 40 E., Mt. Diablo Mer., bears N.  $2^{\circ}32^{'}46^{"}$  W., 2,628.41 ft. dist., monumented with a U.S.G.L.O. brass cap,  $2^{\frac{1}{2}}$  ins. diam., mkd. S27, S28, S33, S34, T. 28 N., R. 40 E., 1921, set in an iron pipe, 2 ins. diam., 11 ins. above ground, and surrounded by a scattered rock mound. Rebuilt the rock mound and left a 5 ft. steel guard post.

The ¼ cor. bet. secs. 33 and 34, T. 28 N., R. 40 E., Mt. Diablo Mer., bears S. 84°28'02" W., 118.27 ft. dist., monumented with a U.S.G.L.O. brass cap mkd. ¼ S33, S34, 1921, set in an iron pipe, 1 in. diam., 5 ins. above ground. Left a 5 ft. steel guard post.

A cor. of the location bears N.  $78^{\circ}08'$  W., 3.1 ft. dist.

No local bearing objects or bearing trees available.

Thence S. 78°08'19" E.

270.

Top of bluff, bears N. 44° E. and S. 44° W.

473.

Center of wash, course S. 49° W.

1497.46

Cor. No. 2, identical with Cor. No. 4 of the Carol #2 lode of this survey.

Set an iron post, 24 ins. long, 2 ins. diam., 21 ins. in the ground, with a brass cap mkd. C1-2-C2-4-4949.

No local bearing objects or bearing trees available.

Thence S. 11°21'41" W.