

Mineral Survey No. 4951

FEET	
	RUTH #1 LODE
	At Cor. No. 1 of the Ruth #1 lode, identical with Cor. No. 1 of the Ruth #2 lode of this survey.
	Set an iron post, 24 ins. long, 2 ins. diam., 22 ins. in the ground, with a brass cap mkd. R1-1-R2-1-4951; from which
	The $\frac{1}{4}$ cor. of secs. 4 and 9, T. 27 N., R. 40 E., Mt. Diablo Mer., bears S. $71^{\circ}13'50''$ E., 1,032.90 ft. dist., monumented with a U.S.G.L.O. brass cap, $2\frac{1}{2}$ ins. diam., mkd. $\frac{1}{4}$, S4, S9, 1929, set in an iron pipe, 1 in. diam., 19 ins. above ground. Set steel fence post alongside.
	The cor. of secs. 4, 5, 8, and 9, T. 27 N., R. 40 E., Mt. Diablo Mer., bears S. $78^{\circ}46'27''$ W., 1,695.17 ft. dist., monumented with a U.S.G.L.O. brass cap, $2\frac{1}{2}$ ins. diam., mkd. S5-S4-S8-S9, set in an iron pipe, 2 ins. diam., 9 ins. above ground.
	No local bearing objects or bearing trees available.
	Thence S. $48^{\circ}57'12''$ E.
658.	Center of road, 16 ft. wide, bears N. 65° W. and S. 71° E.
1050.	Center of wash, course N. 73° W.
1499.63	Cor. No. 2, identical with Cor. No. 4 of the Ruth #2 lode of this survey.
	Set an iron post, 24 ins. long, 2 ins. diam., 22 ins. in the ground, with a brass cap mkd. R1-2-R2-4-4951.
	No local bearing objects or bearing trees available.
	Thence S. $41^{\circ}02'52''$ W.
50.	Top of bluff, bears N. 84° W. and S. 84° E.
230.	Top of ridge, bears N. 80° W. and S. 80° E.
300.00	Lode line; discovery point bears N. $48^{\circ}57'12''$ W., 750.00 ft. dist.