

Mineral Survey No. 4935

	FEET	Set an iron pipe, 36 ins. long, 1 in. diam., 4 ins. in the ground to bedrock and in a mound of stone, with a brass cap, mkd. M 7-1-M 8-1-4935; from which The $\frac{1}{4}$ section corner common to sections 13, and 14, T. 16 N., R. 24 E., MDM, bears S. $86^{\circ} 11' 49''$ W., 732.58 ft. dist., monumented with an iron post, 1 in. diam., 24 ins. above ground, firmly set, with brass cap, properly mkd., in a mound of stone. No local bearing objects or bearing trees available. Thence N. $85^{\circ} 33' 03''$ E.
102		Center of dry gully, 8 ft. wide, course S. 45° E.
300.00		Lode line; discovery point bears N. $2^{\circ} 10' 33''$ E., 575.00 ft. dist.
327		Center of wide wash, drains N. 40° E.
589.15		Cor. No. 2. Set an iron pipe, 36 ins. long, 1 in. diam., 14 ins. in the ground, in a mound of stone, with a brass cap mkd. M 7-2-4935. No local bearing objects or bearing trees available. Thence N. $2^{\circ} 10' 33''$ E.
1494.75		Cor. No. 3. Set an iron pipe, 36 ins. long, 1 in. diam., 18 ins. in the ground, in a mound of stone with a brass cap mkd. M 7-3-4935. No local bearing objects or bearing trees available. Thence S. $85^{\circ} 33' 03''$ W.
289.15		Lode line, discovery point bears S. $2^{\circ} 10' 33''$ W., 919.75 ft. dist.
408		Dry gully, 20 ft. wide, drains N. 35° E.
589.15		Cor. No. 4, identical with Cor. No. 4, of the Momi #8 lode of this survey. Set an iron pipe, 36 ins. long, 1 in. diam., 12 ins. in bedrock, in a mound of stone, with a brass cap mkd. M 7-4-M 8-4-4935.