

FEET	
	<p>vey, and on line 3-4 M.S. No. 4925A SEGO #1 lode.</p> <p>Set an iron rod, 2 ft. long, 5/8 inch diam., 18 ins. in the ground, in a mound of stone, with aluminum cap mkd. D28-1-D29-1-D143-4976-S1-4925A; from which</p> <p>The Cor. of Ts. 27N. and 28N., and Rs. 45E. and 46E., M.D.M. bears S.36°01'22"E., 12,376.51 ft. dist., monumented with an iron post, 3 ins. diam., 12 ins. above the ground, firmly set with brass cap properly mkd., and with a mound of stone, 3 ft. in diam.</p> <p>No local bearing objects or bearing trees available.</p> <p style="text-align: center;">Thence S.38°32'40"W.</p>
72.84	Cor. No. 3 of the DMS 143 millsite, identical with Cor. No. 3 of the DMS 144 millsite of this survey, and on line 3-4 M.S. No. 4925A SEGO #1 lode.
76.00	Top edge of ore dump.
283.00	Base of ore dump.
363.99	<p>Cor. No. 2, identical with Cor. No. 4 of the DMS 144 millsite, on line 2-3 of the DMS 51 millsite of this survey, and Cor. No. 4, M.S. No. 4925A SEGO #1 lode.</p> <p>An existing iron pipe, 1 in. diam., 13 ins. above ground, surrounded by a rock mound, 2 ft. diam., with a brass cap mkd. S1-4-4925A. Remarked brass cap D28-2-D144-4-D51-4976-S1-4-4925A.</p> <p>No local bearing objects or bearing trees available.</p> <p style="text-align: center;">Thence N.51°44'24"W.</p>
4.00	Center of ravine, bears S.49°W.
153.00	Center of ravine, bears S.2°E.
258.00	Center of road, 25 ft. wide, bears N.8°E. and S.8°W.
327.92	Cor. No. 2 of the DMS 51 millsite, identical with Cor. No. 2 of the DMS 76 millsite of this survey.
551.00	Center line of power line, bears S.18°E. and N.18°W.
598.36	Cor. No. 3, on line 2-3 of the DMS 76 millsite of this survey.