

FEET	
	<p>and Cor. No. 3 of the DMS 133 millsite of this survey.</p> <p>Set an iron rod, 2 ft. long, 5/8 inch diam., 18 ins. in the ground, in a mound of stone, with aluminum cap mkd., DA15-1-D135-1-D133-3-4977A-B; from which</p> <p style="padding-left: 40px;">The Cor. of Ts. 27N. &amp; 28N., Rs. 45E. and 46E., M.D.M. bears S.5°05'23"E., 4,673.88 ft. dist., monumented with an iron post, 3 ins. diam., 12 ins. above the ground, firmly set with a brass cap properly mkd., and with a mound of stone, 3 ft. in diam.</p> <p>No local bearing objects or bearing trees available.</p> <p style="padding-left: 40px;">Thence N.36°46'30"E.</p>
187.00	Center of ravine, bears N.61°E.
299.93	Lode line; discovery point bears S.53°23'30"E., 810.00 ft. dist.
304.00	Center of road, 21 ft. wide, bears N.80°E. and S.80°W.
599.85	<p>Cor. No. 2, identical with Cor. No. 4 of the DMS 133 millsite, and Cor. No 5 of the DMS 131 millsite of this survey.</p> <p>Set an iron rod, 2 ft. long, 5/8 inch diam., 18 ins. in the ground, in a mound of stone, with aluminum cap mkd., DA15-2-D133-4-D131-5-4977A-B.</p> <p>No local bearing objects or bearing trees available.</p> <p style="padding-left: 40px;">Thence S.53°23'30"E.</p>
217.00	Center of road, 21 ft. wide, bears N.69°E. and S.69°W.
272.00	Center of ravine, bears N.83°E.
597.10	Cor. No. 4 of the DMS 131 millsite of this survey.
698.00	Center of road, 12 ft. wide, bears N.34°E. and S.34°W.
779.00	Center of road, 10 ft. wide, bears S.65°E. and N.65°W.
867.00	Center of ravine, bears N.41°E.
1063.00	Center of road, 12 ft. wide, bears S.11°W. and N.11°E.
1184.00	Center of ravine, bears N.13°E.