

Mineral Survey No. 4997

FEET	
	THERE NO. 1 LODE
	At Cor No. 1 of the There No. 1 lode, identical with Cor. No. 1 of the There No. 3 lode of this survey.
	This point falls on top of buried pipeline, unsuitable for monumentation.
	The NW Cor. of Sec. 2, T. 33 N., R. 51 E., Mt. Diablo Mer., bears N. 21°21'03" W., 1579.76 ft. dist., monumented with an iron pipe, 2 ins. diam., ½ ins. above ground, with mkd. brass cap.
	Thence N. 0°03'56" W.
810	Enter ore stockpile, edge bears N. 27° E. and S. 9°30' W.
910	Center of road, 40 ft. wide, bears N. 22° E. and S. 22° W.
1005	Leave ore stockpile, edge bears N. 63° E. and S. 63° W.
1470.61	Intersect the line between Secs. 2 and 35 at a point from which the NW cor. of Sec. 2 bears N. 89°56'35" W., 573.46 ft. dist., monumented with a brass cap, ½ in. above the ground.
1495.88	Cor. No. 2, identical with Cor. No. 2 of the There No. 3 lode of this survey. Set an iron post, 24 ins. long, 2 ins. diam., 17 ins. in the ground, with a brass cap mkd. T1-2-T3-2-4997-1983; from which A cor. of the location bears N. 67°49' E., 1.3 ft. dist. No local bearing objects or bearing trees available. Thence S. 89°57'17" W.
300.00	Lode line; discovery point bears S. 0°04'55" E., 1449.05 ft. dist.
359.70	Enter shop building, 60 ft. x 76 ft., at a point from which the SE cor. bears S. 18°17' W., 48.2 ft. dist.
428.38	Leave shop building, 60 ft. x 76 ft., at a point from which the SW cor. bears S. 18°17' W., 28.1 ft. dist.
600.00	Cor. No. 3, and cor. of location. Set an iron post, 24 ins. long, 2 ins. diam., 16 ins. in the ground, with a brass cap mkd. T1-3-4997-1983; from which