

FEET	
	<p style="text-align: center;">H #24 LODE</p> <p>At Cor. No. 1 of the H #24 lode.</p> <p>Set an iron post, 24 ins. long, 2 ins. diam., 20 ins. in the ground, with a brass cap mkd. H24-1-4952; from which</p> <p>The cor. of secs. 25, 26, 35 and 36, T. 41 N., R. 53 E., Mt. Diablo Mer., bears N. 82°27'32" E., 11,999.78 ft. dist.; monumented with a rock, 9 ins. x 3 ins. x 10 ins. above ground, with small mound of rock 1.0 ft. West. No marks or notches visible. 30 ins. steel guard post alongside.</p> <p>The NE Cor. of Sec. 2, T. 40 N., R. 53 E., Mt. Diablo Mer., bears S. 73°14'39" E., 12,697.28 ft. dist.; monumented with a rock, 12 ins. x 16 ins. x 6 ins. above the ground, with 4 visible marks on the west side. 30 ins. steel guard post alongside.</p> <p>No local bearing objects or bearing trees available.</p> <p style="text-align: center;">Thence S. 0°17'08" E.</p>
300.00	Lode line; discovery point bears S. 89°42'52" W., 100 ft. dist.
600.00	<p>Cor. No. 2, identical with Cor. No. 4 of the H #1 lode of this survey.</p> <p>Set an iron post, 24 ins. long, 2 ins. diam., 20 ins. in the ground, with a brass cap mkd. H24-2-H1-4-4952.</p> <p>No local bearing objects or bearing trees available.</p> <p style="text-align: center;">Thence S. 89°42'52" W.</p>
1020.	Center of main road, 20 ft. wide, bears N. 56° E. and S. 56° W.
1500.00	<p>Cor. No. 3, identical with Cor. No. 3 of the H #1 lode of this survey.</p> <p>Set an iron post, 24 ins. long, 2 ins. diam., 15 ins. in the ground, with a brass cap mkd. H24-3-H1-3-4952.</p> <p>No local bearing objects or bearing trees available.</p> <p style="text-align: center;">Thence N. 0°17'08" W.</p>
300.00	Lode line; discovery point bears N. 89°42'52" E., 1,400 ft. dist.