

FEET	
	<p>The cor. of secs. 22, 23, 26, and 27, T. 22 N., R. 49 E., MDM, bears N. 31°24'26" W., 2823.40 ft. dist.; monumented with an aluminum pipe, 2 1/2 ins. diam. and cap 3 ins. diam., properly marked and 7 ins. above ground in a mound of stone, reestablished by Nevada LS No. 5830.</p> <p>No local bearing objects or bearing trees available.</p> <p>Thence N. 45°07'01" E.</p>
1500.00	<p>Cor. No. 2, identical with Cor. No. 4 of the WAH 31 lode of this survey.</p> <p>Set a flanged aluminum pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with a 3 ins. diam. aluminum cap mkd. WAH29-2-WAH31-4-5004.</p> <p>No local bearing objects or bearing trees available.</p> <p>Thence S. 44°50'29" E.</p>
300.00	<p>Lode line; discovery point bears S. 45°07'01" W., 1490.00 ft. dist.</p>
600.00	<p>Cor. No. 3.</p> <p>Set a flanged aluminum pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and with a mound of stone, 4 ft. base, 3ft. high, E of cor., and with 3 ins. diam. aluminum cap mkd. WAH29-3-5004.</p> <p>No local bearing objects or bearing trees available.</p> <p>Thence S. 45°07'01" W.</p>
1500.00	<p>Cor. No. 4.</p> <p>Set a flanged aluminum pipe, 30 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with a 3 ins. diam. aluminum cap mkd. WAH29-4-5004.</p> <p>No local bearing objects or bearing trees available.</p> <p>Thence N. 44°50'29" W.</p>
300.00	<p>Lode line; discovery point bears N. 45°07'01" E., 10.00 ft. dist.</p>
600.00	<p>Cor. No. 1, and place of beginning.</p>
	<hr/> <p>WAH 31 LODE</p> <p>Beginning at Cor. No. 1 of the WAH 31 lode,</p>