

MINERAL SURVEY NO. 4984

FEET	ROYAL PEACOCK BLACK I
	<p>At Corner No. 1 of the ROYAL PEACOCK BLACK I lode, identical with the Northeast Corner of Section 4, T. 45 N., R. 26 E., M.D.B. & M., monumented with a firmly set basalt rock, 10 inches x 15 inches, 6 inches out of the ground, marked C.C., with three notches chiseled on the East side and three notches chiseled on the West side. Removed the rock and in its place set an Iron Post, 24 inches long and 2 inches in diameter, 20 inches in the ground, with a Brass Cap marked RPBI-1 MS 4984 C.C. $\frac{S32}{S4 S3}$</p> <p>T. 45 N., R. 26 E., M.D.B. & M. 1986 Placed original stone alongside.</p> <p>No local bearing objects or bearing trees available.</p>
	<p>THENCE, S 3°31'46" E</p>
125.	Center of road, 11 feet wide, bearing S 78°10' E and N 78°10' W.
144.	Center of draw, 80 feet wide, drains N 70°44' E.
387.	Top of ridge bearing N 18°31' E and S 18°31' W.
529.	Center of draw, 20 feet wide, drains N 31°43' E.
767.	Top of ridge bearing N 77°40' E and S 77°40' W.
941.	Top of ridge bearing N 85°34' E and S 85°34' W.
1,140.	Center of draw, 30 feet wide, drains S 46°08' E.
1,271.	Top of ridge bearing N 86°30' E and S 86°30' W.
1,454.	Center of draw, 60 feet wide, drains N 83°01' E.
1,500.00	<p>Corner No. 2.</p> <p>Set an Iron Post, 24 inches long, 2 inches in diameter, 15 inches in the ground, surrounded by a rock mound 3 feet in diameter, with a Brass Cap marked RPBI-2 M.S. 4984 1986; from which</p> <p>A corner of the location bears S 3°31'46" E, 83.33 feet distant.</p>