Mineral Survey No. 5001

	Mineral Survey No. 5001
FEET	
	All lines and connections of this survey were run by direct methods.
	The magnetic declination observed at each corner of the survey gave a uniform value of 17°30'E.
	Mineral Survey No. 5001
	M 431 MILLSITE
	At Cor. No. 1 of the M 431 millsite.
	Set an iron post, 30 ins. long, 3/4 in. diam., 18 ins. in the ground, in a concrete and rock base, with a brass cap firmly secured to the iron post, mkd. X M.431 1 U.S.M.S. 5001; from which
	Cor. No. 2, M.S. No. 5000 (unapproved) M 327 mill site, bears N.75°31'30"E., 1,500.75 ft. dist.
	The cor. of secs. 17, 18, 19 & 20, T.27 N., R.48 E., M.D.M., bears S.66°19'25"E., 11,544.65 ft. dist., monumented with a mkd. stone, 8 x 12 ins., 14 ins. above ground, markings illegible. Two steel fence posts stand adjacent.
	A wood post, 4 x 4 ins. in size, 4 ft. above ground, sets adjacent to the iron post.
	No local bearing objects or bearing trees avail- able.
	Thence S.75°31'30"W.
300.15	Cor. No. 2.
	Set an iron post, 30 ins. long, 3/4 in. diam., 18 ins. in the ground, in a concrete and rock base, with a brass cap firmly secured to the iron post, mkd. X M.431 2 U.S.M.S. 5001; from which
	A wood post, 4 x 4 ins. in size, 4 ft. above ground, sets adjacent to the iron post.
	No local bearing objects or bearing trees avail- able.
	Thence N.14°28'30"W.
724.50	Cor. No. 3.
	Set an iron post, 30 ins. long, 3/4 in. diam., 18 ins. in the ground, in a concrete and rock base, with a brass cap firmly secured to the iron post, mkd. X M.431 3 U.S.M.S. 5001; from which
	A wood post, 4 x 4 ins. in size, 4 ft. above ground, sets adjacent to the iron post.

,

2