

Mineral Survey No. 5020

FEET

The measured horizontal angle right at the W 1/4 sec. cor. Sec. 35, T. 34 N., R. 51 E., M.D.M., with backsight from NGC Control Pt. No. TT-249, 2559.32 ft. dist. toward Cor. No. 1 of the POINT TOO lode is $53^{\circ}57'41''$, 2713.36 ft. dist. The measured horizontal angle right at Cor. No. 1 of the POINT TOO lode of this survey with backsight from W 1/4 sec. cor. Sec. 35, toward Cor. No. 2 of the POINT TOO lode is $359^{\circ}15'07''$. The resulting bearing of line 1-2 of the POINT TOO lode is NORTH.

All lines and connections of this survey were run by direct methods except as noted.

The latitude and longitude for Cor. No. 1, POINT TOO lode was found to be $40^{\circ}47'00''$ N. and $116^{\circ}13'06''$ W.

The magnetic declination observed at each cor. gave a uniform value of $17^{\circ}30'E$.

POINT TOO LODE

At Cor. No. 1 of the POINT TOO lode.

The point for this corner is located in an active area of an open pit mine, cor. not set; from which

The W 1/4 sec. cor. of Sec. 35, T. 34 N., R. 51 E., Mt. Diablo Meridian bears N. $0^{\circ}44'53''$ E., 2713.36 ft. dist., monumented with a properly mkd. U.S.G.L.O. brass cap, 15 ins. above ground and in a rock mound.

Cor. No. 3, M.S. No. 4998 KL-5 lode, identical with Cor. No. 3, M.S. No. 4998 KL-6 lode, bears N. $0^{\circ}44'40''$ E., 2699.16 ft. dist., monumented with a properly mkd. brass cap, 9 ins. above the ground.

Cor. No. 4, M.S. No. 4997 There No. 1 lode, bears S. $2^{\circ}09'33''$ E., 1456.53 ft. dist., monumented with a properly mkd. brass cap, 11 ins. above the ground, surrounded by a rock mound.

No local bearing objects or bearing trees available.

Thence NORTH