

Mineral Survey No. 5022

FEET	
	BD 424 LODE At Cor. No. 1 of the BD 424 lode. Set an iron post, 24 ins. long, 2 ins. diam., 20 ins. in the ground, with a brass cap mkd. BD424-1-5022; from which The N$\frac{1}{4}$ sec. cor. of Sec. 10, T. 10 N., R. 36 E., Mt. Diablo Meridian, bears N. 19°28'18" W., 2,773.84 ft. dist., monumented with an aluminum post and properly mkd. aluminum cap, 23 ins. above ground, surrounded by a mound of stone, 4 ft. diam. No local bearing objects or bearing trees available. Thence N. 45°37'04" W.
300.00	Lode line; discovery point bears S. 44°21'04" W., 10.0 ft. dist.
600.00	Cor. No. 2, identical with Cor. No. 2 of the BD 426 lode of this survey. Set an iron post, 24 ins. long, 2 ins. diam., 19 ins. in the ground, with a brass cap mkd. BD424-2-BD426-2-5022. No local bearing objects or bearing trees available. Thence S. 44°21'04" W.
1382.	Center of road, 30 ft. wide, bears N. 31°44' W., and S. 31°44' E.
1415.	Power line, bears N. 31°44' W. and S. 31°44' E.
1497.41	Cor. No. 3, on line 2-3 of the BD 426 lode of this survey. Set an iron post, 24 ins. long, 2 ins. diam., 22 ins. in the ground, with a brass cap mkd. BD424-3-5022. No local bearing objects or bearing trees available. Thence S. 45°37'04" E.
300.00	Lode line; discovery point bears N. 44°21'04" E., 1,487.41 ft. dist.