

FEET		
300.00	Lode line; discovery point bears N. 44°20'52" E., 70.0 ft. dist.	
600.00	Cor. No. 4. Set an iron post, 24 ins. long, 2 ins. diam., 18 ins. in the ground, with a brass cap mkd. BD440-4-5023. No local bearing objects or bearing trees available.	
240.	Center of road, 15 ft. wide, bears N. 51° W. and S. 51° E.	
1500.00	Cor. No. 1, and place of beginning.	
	BD 443A LODE	
	Beginning at Cor. No. 1, identical with Cor. No. 1 of the BD 440 lode and Cor. No. 1 of the BD 442A lode, both of this survey, hereinbefore described.	
	Thence N. 45°36'40" W.	
300.00	Lode line; discovery point bears N. 45°01'26" E., 10.0 ft. dist.	
420.	Center of road, 30 ft. wide, bears N. 85° E. and S. 85° W.	
600.00	Cor. No. 2, identical with Cor. No. 2 of the BD 440 lode of this survey, hereinbefore described.	
	Thence N. 45°01'26" E.	
380.	Center of road, 30 ft. wide, bears N. 10° W. and S. 20° E.	
718.	Wire fence, 6 ft. high, bears N. 1° E. and S. 1° W.	
1500.00	Cor. No. 3. Set an iron post, 24 ins. long, 2 ins. diam., 19 ins. in the ground, with a brass cap mkd. BD443A-3-5023; from which The W $\frac{1}{4}$ sec. cor. Sec. 3, T. 10 N., R. 36 E., bears N. 52°20'38" E., 2,054.85 ft. dist., monumented with an aluminum post and properly mkd. aluminum cap, 7 ins. above the ground.	